



**PLUMBING:**

- 20mm NB(3/4") HOT & COLD WATER SUPPLY LINES MAX PRESSURE 7 BAR (100 PSI) 4 BAR (60 PSI) TO 5 BAR (70 PSI) RECOMMENDED. FIT SHUT OFF VALVES AND SERVICEABLE STRAINERS IN WATER SUPPLY LINES.
- 50mm (2") FLOOR DRAIN FOR ROOM.
- 50mm (2") DRAIN FOR TABLE DRAIN CONNECTION.
- APPROXIMATELY 400 LITRES (100 GALLONS) USED FOR A (20) TWENTY MINUTE TREATMENT. BASED UPON HYDROCO TREATMENT ASSUME 200 LITRES (50 GALLONS) OF THIS BEING HOT WATER BASED ON THE EXPECTED NUMBER OF TREATMENTS DAILY AN APPROPRIATE HOT WATER SUPPLY NEEDS TO BE INSTALLED.

**NOTE:** INSTALL IN ACCORDANCE WITH LOCAL AND NATIONAL CODE REQUIREMENTS.

**LEGEND:**

- ⊕ 50mm (2") FLOOR DRAIN - FOR TABLE DRAIN CONNECTION
- ⊕ 50mm (2") FLOOR DRAIN - FOR ROOM DRAIN
- HW ⊕ 20mm (3/4") HOT WATER CONNECTION
- CW ⊕ 20mm (3/4") COLD WATER CONNECTION
- ⊕ 40mm (1 1/2") TABLE DRAIN (IN TABLE)

**HYDROCO (AUST) PTY LTD**

SEAFORD VICTORIA AUSTRALIA

ph.+61 3 8770 4000 www.hydroco.com fax.+61 3 9773 6122

**HYDROWOOD 7 - LAYOUT SPECIFICATION**

DRG No.HW-INST-003

NOTE! THIS DRAWING IS TO BE USED AS A GUIDE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE

16 OCT 2007